BRYANT®

Combination Devices, Residential Grade, Decorator Series, 1) Single Pole Rocker, 1) Tamper Resistant Single Receptacle, 15A 12OV AC, Side Wired

By Bryant Catalog # RCD108BKTR

Switches and Lighting Controls, Combination Devices, Residential Grade, Decorator Series, 1) Single Pole Rocker, 1) Tamper Resistant Single Receptacle, 15A 120V AC, Side Wired



Residential

Performance

- Electrical Dielectric voltage Withstands 1,500V AC minimum for 1 minute
- Electrical Endurance 30,000 cycles minimum
- Electrical Max. working voltage 120V
- Electrical Overload 1.5 times rating
- Environmental Flammability UL VO
- Environmental Operating temperatures Maximum continuous 60°C
- minimum -20°C (without impact)
- Mechanical Terminal accommodation Back and side wire: #14 AWG min. - #12 AWG max. solid and stranded copper wire only
- push wire: #14 AWG solid copper wire only

General

Action Snap Switch
Actuator Rocker
Catalog Number RCD108BKTR
Contact Configuration Two Position
EU RoHS Indicator Yes

Environmental Conditions Indoor Dry Unless Protected By

Additional Means

Mounting Screws

Item Type Decorator Switch and

Receptacle Combo Devices

Material - Mounting Hardware

Number Of Poles 1) Single Pole
Operating Cycles 30,000 Minimum

Operating Temperature Max Continuous- 60 Degrees C,

Minimum - -20 Without Impact



Specifications • Base and body - PVC

• Mounting strap - Galvanized steel

Rocker - Polycarbonate

Terminal screws - Steel

• Terminals - Brass UPC 883778302343

Dimensions

Display Size Standard Size

Electrical Ratings

Amperage Rating 15 A Connectivity Side Wired Contact Rating 15A Current / Amperage Rating 15 A Current Rating 15 A 125 VAC Voltage Rating Voltage Rating Description 125 VAC Wattage 1875

Certifications And Compliance

Industry Standard(s) • CSA Certified

• UL Listed E3896

Logistics

Carton Quantity 10

Product Assets

Catalog Page - WDK Z-4 Catalog Page Catalogs - WDK Catalog Full 2024 Catalogs - Bryant Full Line Catalog Specifications - RCD108BKTR

