BRYANT®

TradeSelect, Straight Blade, Single Receptacle, Self Grounding, 15A 125V, 2-Pole 3-Wire Grounding, 5-15R, Black

By Bryant Catalog # RR151BK

tradeSELECT* Straight Blade, Single Receptacle, Self Grounding, 15A 125V, 2-Pole 3-Wire Grounding, 5-15R



Features

- Smooth indented face appearance
- Multiple-drive Slot/Phillips/Robertson head screws
- Tough thermoplastic ultrasonically welded cover and base

Application

Residential Receptacles

General

Color

- Black
- Noir

Environmental Conditions

Item Type Material

Material - Mounting Hardware

Number Of Poles Performance Indoor Dry Unless Protected

Single

Thermoplastic

Screw Mounting

By Additional Means

2-Pole

 Environmental - Operating temperature - -20°C to

60°C

 Mechanical - Terminal -Terminal screws accepts up to #12 AWG, Push wire designed for #14 AWG solid copper wire only

UPC 883778110627

Dimensions

Display Size Standard Sized Product

Electrical Ratings

Amperage Rating 15 A

Connectivity Side Wired

Current / Amperage Rating 15 A

Current Rating 15 A

Phase Single Phase
Voltage Rating 125 VAC
Voltage Rating Description 125 VAC

Wattage 1875

Conductor Related

Number Of Wires 3-Wire Grounding
Wire Size #14 AWG to #12 AWG

Certifications and Compliance

Nema Rating 5-15R

Logistics

Carton Quantity 10

Product Assets

Catalog Page - Bryant A-19 Catalog page Catalogs - Bryant Full Line Catalog

