BRYANT®

TradeSelect, Straight Blade, Duplex Receptacle, Tamper Resistant, Quick Wire Push Terminals, 15A 125V, 2- Pole 3-Wire Grounding, 5-15R, Light Almond

By Bryant Catalog # RR15EQLATR

TradeSelect, Straight Blade, Duplex Receptacle, Tamper Resistant, Quick Wire Push Terminals, 15A 125V, 2- Pole 3-Wire Grounding, 5-15R, Light Almond

Features

- Smooth indented face appearance
- · Tough thermoplastic ultrasonically welded cover and base
- Elongated strap with continuous plaster ears to secure device

Application

Residential Receptacles

Performance

- Environmental Operating temperature -20°C to 60°C
- Mechanical Terminal Terminal screws accepts up to #12 AWG, Push wire designed for #14 AWG solid copper wire only

General

Catalog Number Color EU RoHS Indicator **Environmental Conditions**

Item Type Material Material - Mounting Hardware Number Of Poles Specifications

RR15EQLATR Light Almond No Indoor Dry Unless Protected By Additional Means **Traditional Duplex** Thermoplastic Screw Mounting 2-Pole

- Base and Cover Tough thermoplastic
- Product Type Receptacle
- Receptacle Type Duplex Quick Thread
- Spring Material Stainless Steel
- 883778301391



Dimensions

Display Size

Standard Sized Product

Eight Push Wire Holes

15 A

15 A

15 A

1875

Single Phase

125 VAC

125 VAC

Electrical Ratings

Amperage Rating Connectivity Current / Amperage Rating **Current Rating** Phase Voltage Rating Voltage Rating Description Wattage

Conductor Related

Number Of Wires Wire Size

3-Wire Grounding #14 AWG to #12 AWG

Certifications And Compliance

Industry Standard(s)	CSA Certified
	• UL Listed E2186
Nema Rating	5-15R

Logistics

Carton Quantity 10

Product Assets

Catalog Page - BRY A-18 Catalog Page Catalogs - Bryant Full Line Catalog Specifications - RR15EQLATR



UPC