BRYANT[®]

TradeSelect, Straight Blade, Duplex Receptacle, Tamper Resistant, Cut Ears, 15A 125V, 2-Pole 3-Wire Grounding, 5-15R, Brown

By Bryant Catalog # RR15KTR

TradeSelect, Straight Blade, Duplex Receptacle, Tamper Resistant, Cut Ears, 15A 125V, 2-Pole 3-Wire Grounding, 5-15R, Brown

Features

- Smooth indented face appearance
- Multiple-drive Slot/Phillips/Robertson head screws
- Tough thermoplastic ultrasonically welded cover and base

Application

Residential Receptacles

Performance

- Environmental Operating temperature -20°C to 60°C
- Mechanical Terminal Terminal screws accepts up to #12 AWG, Push wire designed for #14 AWG solid copper wire only

General

Catalog Number Color EU RoHS Indicator Environmental Conditions

Item Type Material Material - Mounting Hardware Number Of Poles Specifications RR15KTR Brown Yes Indoor Dry Unless Protected By Additional Means Traditional Duplex Thermoplastic Screw Mounting 2-Pole • Material - Thermoplastic

- Number of Poles 2 Pole
- Product Type Receptacle
- Receptacle Type Duplex 883778301698



Dimensions

Display Size

Electrical Ratings

Amperage Rating 15 A **Eight Push Wire Holes** Connectivity Current / Amperage Rating 15 A Current Rating 15 A Phase Single Phase Voltage Rating 125 VAC Voltage Rating Description 125 VAC Wattage 1875

Conductor Related

Number Of Wires3-Wire GroundingWire Size#14 AWG to #12 AWG

Standard Sized Product

Certifications And Compliance

Nema Rating 5-15R

Logistics

Carton Quantity 100

Product Assets

Catalog Page - BRY A-18 Catalog Page Catalogs - Bryant Full Line Catalog Specifications - RR15KTR



UPC