BRYANT®

TradeSelect, Straight Blade Devices, Receptacles, Residential Grade, Weather and Tamper Resistant Duplex, 15A 125V, 5-15R

By Bryant Catalog # RR15SBKWRTR

TradeSelect, Straight Blade Devices, Receptacles, Residential Grade, Weather and Tamper Resistant Duplex, 15A 125V, 2-Pole 3-Wire Grounding, 5-15R, Self Grounding, Black

Features

- Smooth indented face appearance
- Multiple-drive Slot/Phillips/Robertson head screws
- Tough thermoplastic ultrasonically welded cover and base

Application

Residential Receptacles

Performance

- Environmental Operating temperature -20°C to 60°C
- Mechanical Terminal Terminal screws accepts up to #12 AWG, Push wire designed for #14 AWG solid copper wire only

General

Catalog Number Color EU RoHS Indicator Environmental Conditions Item Type Material Material - Mounting Hardware Number Of Poles Specifications RR15SBKWRTR Black No Weather Resistant Traditional Duplex Thermoplastic Screw Mounting 2-Pole • Material - Thermoplastic

- Number of Poles 2 Pole
- Product Type Receptacle
- Receptacle Type Duplex

883778303012

Dimensions

UPC



Display Size

Standard Sized Product

Electrical Ratings

Amperage Rating 15 A Push and Side Wire Connectivity Current / Amperage Rating 15 A **Current Rating** 15 A Single Phase Phase 125 VAC Voltage Rating Voltage Rating Description 125 VAC Wattage 1875

Conductor Related

Number Of Wires Wire Size

3-Wire Grounding #14 AWG to #12 AWG

5-15R

Certifications And Compliance

Nema Rating

Logistics

Carton Quantity	10
Pallet Quantity	9000

Product Assets

Catalog Page - WDK Z-16 Catalog Page Catalogs - WDK Catalog Full 2024 Catalogs - Bryant Full Line Catalog Specifications - RR15SBKWRTR

