BRYANT®

TradeSelect, Straight Blade, Single **Receptacle, Weather and Tamper** Resistant, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R, Gray

By Bryant Catalog # RR201GYWRTR

TradeSelect, Straight Blade, Single Receptacle, Weather and Tamper Resistant, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R, Gray

Features

Application

Residential Receptacles

Performance

- Environmental Operating temperature -20°C to 60°C
- Mechanical Terminal Terminal screws accepts up to #12 AWG, Push wire designed for #14 AWG solid copper wire only

General

Catalog Number Color EU RoHS Indicator **Environmental Conditions** Item Type Material Material - Mounting Hardware Number Of Poles Specifications

RR201GYWRTR Gray No Weather Resistant Single Thermoplastic Screw Mounting 2-Pole • Material - Thermoplastic

- Number of Poles 2 Pole
- Product Type Receptacle
- Receptacle Type Single
- 883778302954

Dimensions

UPC



Display Size

Standard Sized Product

Electrical Ratings

Amperage Rating 20 A Side Wired Connectivity Current / Amperage Rating 20 A **Current Rating** 20 A Single Phase Phase 125 VAC Voltage Rating Voltage Rating Description 125 VAC Wattage 2500

Conductor Related

Number Of Wires Wire Size

3-Wire Grounding #12 AWG to #10 AWG

Certifications And Compliance

5-20R

Logistics

Nema Rating

Carton Quantity 10

Product Assets

Catalog Page - WDK Z-17 Catalog Page Catalogs - WDK Catalog Full 2024 Catalogs - Bryant Full Line Catalog Specifications - RR201GYWRTR

