BRYANT®

TradeSelect, Straight Blade, Single Receptacle, Weather and Tamper Resistant, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R, Light Almond

By Bryant Catalog # RR201LAWRTR

TradeSelect, Straight Blade, Single Receptacle, Weather and Tamper Resistant, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R, Light Almond

Features

- Smooth indented face appearance
- Multiple-drive Slot/Phillips/Robertson head screws
- Tough thermoplastic ultrasonically welded cover and base

Application

Residential Receptacles

Performance

- Environmental Operating temperature -20°C to 60°C
- Mechanical Terminal Terminal screws accepts up to #12 AWG, Push wire designed for #14 AWG solid copper wire only

General

Catalog Number RR201LAWRTR Color Light Almond **EU RoHS Indicator**

Environmental Conditions Weather Resistant

Item Type Single Material Thermoplastic Material - Mounting Hardware Screw Mounting

Number Of Poles

Specifications • Material - Thermoplastic

2-Pole

• Number of Poles - 2 Pole

• Product Type - Receptacle

• Receptacle Type - Single

883778302978

Dimensions

UPC



Display Size Standard Sized Product

Electrical Ratings

Amperage Rating 20 A Side Wired Connectivity Current / Amperage Rating 20 A **Current Rating** 20 A Phase Single Phase 125 VAC Voltage Rating

Voltage Rating Description 125 VAC Wattage 2500

Conductor Related

Number Of Wires 3-Wire Grounding Wire Size #12 AWG to #10 AWG

Certifications And Compliance

Nema Rating 5-20R

Logistics

Carton Quantity 10

Product Assets

Catalog Page - WDK Z-17 Catalog Page Catalogs - WDK Catalog Full 2024 Catalogs - Bryant Full Line Catalog Literature - Residential Catalog Specifications - RR201LAWRTR

