BRYANT®

TradeSelect, Straight Blade Devices, Residential Grade, Receptacles, Weather and Tamper Resistant Single, 20A 125V, 5-20R

By Bryant Catalog # RR201WWRTR

TradeSelect, Straight Blade Devices, Residential Grade, Receptacles, Weather and Tamper Resistant Single, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R, Self Grounding, White

Features

- Smooth indented face appearance
- Multiple-drive Slot/Phillips/Robertson head screws
- Tough thermoplastic ultrasonically welded cover and base

Application

Residential Receptacles

Performance

- Environmental Operating temperature -20°C to 60°C
- Mechanical Terminal Terminal screws accepts up to #12
 AWG, Push wire designed for #14 AWG solid copper wire only

General

Catalog Number RR201WWRTR White Color **EU RoHS Indicator Environmental Conditions** Weather Resistant Item Type Single Material Thermoplastic Material - Mounting Hardware Screw Mounting Number Of Poles 2-Pole Specifications

Material - ThermoplasticNumber of Poles - 2 Pole

• Product Type - Receptacle

• Receptacle Type - Single

883778302985

Dimensions

UPC



Display Size Standard Sized Product

Electrical Ratings

Amperage Rating 20 A Side Wired Connectivity Current / Amperage Rating 20 A **Current Rating** 20 A Phase Single Phase 125 VAC Voltage Rating Voltage Rating Description 125 VAC Wattage 2500

Conductor Related

Number Of Wires 3-Wire Grounding
Wire Size #12 AWG to #10 AWG

Certifications And Compliance

Nema Rating 5-20R

Logistics

Carton Quantity 10
Pallet Quantity 9000

Product Assets

Catalog Page - WDK Z-17 Catalog Page Catalogs - WDK Catalog Full 2024 Catalogs - Bryant Full Line Catalog Literature - Residential Catalog Specifications - RR201WWRTR

