BRYANT®

TradeSelect, Straight Blade, Single **Receptacle, Self Grounding, 20A** 250V, 2-Pole 3-Wire Grounding, 6-20R, Gray

By Bryant Catalog # RR205GY

TradeSelect, Straight Blade, Single Receptacle, Self Grounding, 20A 250V, 2-Pole 3-Wire Grounding, 6-20R, Gray

Features

- Smooth indented face appearance
- Multiple-drive Slot/Phillips/Robertson head screws
- Tough thermoplastic ultrasonically welded cover and base

Application

Residential Receptacles

General

Color

Gray

Environmental Conditions

- Item Type Material Material - Mounting Hardware Number Of Poles Performance
- Gris Indoor Dry Unless Protected By Additional Means Single

Thermoplastic Screw Mounting

2-Pole

- Environmental Operating temperature - -20°C to 60°C
- Mechanical Terminal -Terminal screws accepts up to #12 AWG. Push wire designed for #14 AWG solid copper wire only

883778300622



Dimensions

Display Size

Standard Sized Product

Electrical Ratings

20 A
Side Wired
20 A
20 A
Single Phas
250V kV
250V kV
5000

Conductor Related

Number Of Wires Wire Size

3-Wire Grounding #12 AWG to #10 AWG

6-20R

10

Phase

Certifications and Compliance

Nema Rating

Logistics

Carton Quantity

Product Assets

Catalog Page - Bryant A-19 Catalog page Catalogs - Bryant Full Line Catalog



UPC