## **BRYANT®**

# TradeSelect, Straight Blade, Single Receptacle, Weather Resistant, 20A 250V, 2-Pole 3-Wire Grounding, 6-20R, Brown

By Bryant Catalog # RR205WR

TradeSelect, Straight Blade, Single Receptacle, Weather Resistant, 20A 250V, 2-Pole 3-Wire Grounding, 6-20R, Brown

## Features

- Smooth indented face appearance
- Multiple-drive Slot/Phillips/Robertson head screws
- Tough thermoplastic ultrasonically welded cover and base

## Application

Residential Receptacles

#### Performance

- Environmental Operating temperature -20°C to 60°C
- Mechanical Terminal Terminal screws accepts up to #12
   AWG, Push wire designed for #14 AWG solid copper wire only

#### General

Catalog Number	RR205WR
Color	Brown
EU RoHS Indicator	No
Environmental Conditions	Weather Resistant
Item Type	Single
Material	Thermoplastic
Material - Mounting Hardware	Screw Mounting
Number Of Poles	2-Pole
Specifications	• Material - Thermoplastic
	• Number of Poles - 2 Pole

Number of Poles - 2 Pole
 Product Type - Receptacle
 Receptacle Type - Single

883778302787

Dimensions

**UPC** 



Display Size Standard Sized Product

## **Electrical Ratings**

Amperage Rating	20 A
Connectivity	Side Wired
Current / Amperage Rating	20 A
Current Rating	20 A
Phase	Single Phase
Voltage Rating	250V kV
Voltage Rating Description	250V kV
Wattage	5000

### **Conductor Related**

Number Of Wires 3-Wire Grounding
Wire Size #12 AWG to #10 AWG

## **Certifications And Compliance**

Nema Rating 6-20R

## Logistics

Carton Quantity 10

#### **Product Assets**

Catalog Page - WDK Z-17 Catalog Page Catalogs - WDK Catalog Full 2024 Catalogs - Bryant Full Line Catalog Specifications - RR205WR

