BRYANT®

Circuit Watch Surge Suppression Straight Blade Receptacle, Industrial/Commercial Grade, 15A 125V, 2-Pole 3-Wire Grounding, 5-15R, Brown

By Bryant
Catalog # SP52A

Circuit Watch Surge Suppression Straight Blade Receptacle, Industrial/Commercial Grade, 15A 125V, 2-Pole 3-Wire Grounding, 5-15R, Brown

Features

- 15A 125V
- 2-Pole 3-Wire Grounding
- 5-15R
- Brown

Application

Duplex with Light and Alarm

General

Catalog Number	SP52A
Color	Blue
EU RoHS Indicator	No
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Indicator(s) Type	LED and Audible Alarm
Item Type	Surge Protection Receptacles
Material	Composite
Material - Mounting Hardware	Mounting Screws
OEM Brand Name	Hubbell Bryant
Operating Temperature	32 Deg F to 140 Deg F (0 Deg C to 60 Deg C)
Outlet	Straight Blade
Response Time	5
Series	Specification Grade
Style	Surge Protection Only
Type	Duplex Receptacle
UPC	781786139008

Dimensions

Display Size	Standard

Electrical Ratings

Amperage Rating	15 A
Connectivity	Terminal Screws
Current / Amperage Rating	15 A
Current Rating	15 A
Frequency Rating	60 Hz
Phase	Single Phase
Voltage Rating	125 V
Voltage Rating Description	125 V

Certifications And Compliance

Nema Rating	5-15R

Logistics

Carton Quantity	10

Product Assets

Catalog Page - BRY D-2 Catalog Page
Catalogs - Bryant Full Line Catalog
Literature - General Literature - Power Disruption Solutions
Literature - General Literature - Duplex Surge Receptacles
Literature - General Literature - Surge Protection Devices
Specifications - SP52A

©2024 Hubbell Incorporated. All rights reserved