# **BRYANT®**

# Circuit Watch Surge Suppression Straight Blade Receptacle, Industrial/Commercial Grade, Isolated Ground, 2-Pole 3-Wire Grounding, 15A 125V, 5-15R

By Bryant Catalog # SP52IGGYA

Circuit Watch Surge Suppression Straight Blade Receptacle, Industrial/Commercial Grade, Isolated Ground, 2-Pole 3-Wire Grounding, 15A 125V, 5-15R, Gray



IG Duplex with Light and Alarm

#### General

Color Gray
EU RoHS Indicator No

Environmental Conditions Indoor Dry Unless Protected

By Additional Means

Indicator(s) Type LED and Audible Alarm
Item Type Surge Protection Receptacles

Material - Mounting Hardware Mounting Screws
OEM Brand Name Hubbell Bryant

Operating Temperature 32 Deg F to 140 Deg F (0 Deg

C to 60 Deg C)

Outlet Straight Blade

Response Time 5

Series Specification Grade
Style Isolated Ground
Type Duplex Receptacle
UPC 781786139145

**Dimensions** 

Display Size Standard

**Electrical Ratings** 

Amperage Rating 15 A

Connectivity Terminal Screws

Current / Amperage Rating 15 A
Current Rating 15 A
Frequency Rating 60 Hz
Phase Single Phase

Voltage Rating 125 V Voltage Rating Description 125 V



### **Certifications and Compliance**

Nema Rating 5-15R

Logistics

Carton Quantity 10

**Product Assets** 

Literature - General Literature - Power Disruption Solutions Literature - General Literature - Duplex Surge Receptacles Literature - General Literature - Surge Protection Devices

## **Related Products**

SP52IGOA - Circuit Watch Surge Suppression Straight Blade Receptacle, Industrial/Commercial Grade, Isolated Ground, 15A 125V, 2- Pole 3-Wire Grounding, 5-15R

SP52GYA - Circuit Watch Surge Suppression Straight Blade Receptacle, Industrial/Commercial Grade, 15A 125V, 2-Pole 3-Wire Grounding, 5-15R, Gray

SP52IA - Circuit Watch Surge Suppression Straight Blade Receptacle, Industrial/Commercial Grade, 15A 125V, 2-Pole 3-Wire Grounding, 5-15R, Ivory

SS26 - Wallplates and Boxes, Metallic Plates, 1- Gang, 1) GFCI Opening, Standard Size, Stainless Steel

SP52IGWA - Circuit Watch Surge Suppression Straight Blade Receptacle, Industrial/Commercial Grade, Isolated Ground, 15A 125V, 2- Pole 3-Wire Grounding, 5-15R

