BRYANT®

Circuit Watch Surge Suppression Straight Blade Receptacle, Industrial/Commercial Grade, Isolated Ground, 15A 125V, 2- Pole 3-Wire Grounding, 5-15R

By Bryant Catalog # SP52IGWA

Circuit Watch Surge Suppression Straight Blade Receptacle, Industrial/Commercial Grade, Isolated Ground, 15A 125V, 2-Pole 3-Wire Grounding, 5-15R, White



Application

IG Duplex with Light and Alarm

General

Color White **EU RoHS Indicator Environmental Conditions** Indoor Dry Unless Protected By Additional Means Indicator(s) Type LED and Audible Alarm Surge Protection Receptacles Item Type Material Composite Material - Mounting Hardware **Mounting Screws**

C to 60 Deg C)

OEM Brand Name Hubbell Bryant 32 Deg F to 140 Deg F (0 Deg Operating Temperature

Outlet Straight Blade

Response Time

Series Specification Grade Isolated Ground Style **Duplex Receptacle** Type UPC 781786139138

Dimensions

Display Size Standard

Electrical Ratings

Amperage Rating 15 A

Terminal Screws Connectivity

Current / Amperage Rating **Current Rating** 15 A Frequency Rating 60 Hz

Phase Single Phase 125 V Voltage Rating

Voltage Rating Description 125 V

Certifications and Compliance

Nema Rating 5-15R

Logistics

Carton Quantity 10

Product Assets

Literature - General Literature - Power Disruption Solutions Literature - General Literature - Duplex Surge Receptacles Literature - General Literature - Surge Protection Devices

Related Products

SP52WA - Circuit Watch Surge Suppression Straight Blade Receptacle, Industrial/Commercial Grade, 15A 125V, 2-Pole 3-Wire Grounding, 5-15R, White

SS26 - Wallplates and Boxes, Metallic Plates, 1- Gang, 1) GFCI Opening, Standard Size, Stainless Steel

P26W - Wallplate, 1-Gang, 1) Decorator, White

SP52GYA - Circuit Watch Surge Suppression Straight Blade Receptacle, Industrial/Commercial Grade, 15A 125V, 2-Pole 3-Wire Grounding, 5-15R, Gray

SP52IA - Circuit Watch Surge Suppression Straight Blade Receptacle, Industrial/Commercial Grade, 15A 125V, 2-Pole 3-Wire Grounding, 5-15R, Ivory

