BRYANT®

Circuit Watch Surge Suppression Straight Blade Receptacle, Hospital Grade, Isolated Ground, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R, Red

By Bryant
Catalog # SP83IGRA

Circuit Watch Surge Suppression Straight Blade Receptacle, Hospital Grade, Isolated Ground, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R, Red



General

Application IG Duplex with Light and Alarm

Catalog Number SP83IGRA
Color Red

EU RoHS Indicator No

Environmental Conditions Indoor Dry Unless Protected By

Additional Means

Indicator(s) Type LED and Audible Alarm
Item Type Surge Protection Receptacles

Material - Mounting Hardware Mounting Screws
OEM Brand Name Hubbell Bryant

Operating Temperature 32 Deg F to 140 Deg F (0 Deg

C to 60 Deg C)

Outlet Straight Blade

Response Time 5

Series Hospital Grade
Style Isolated Ground
Type Duplex Receptacle
UPC 781786154650

Dimensions

Display Size Standard

Electrical Ratings

Amperage Rating 20 A

Connectivity Terminal Screws

125 V

Current / Amperage Rating 20 A
Current Rating 20 A
Frequency Rating 60 Hz
Phase Single Phase
Voltage Rating 125 V

Certifications And Compliance

Voltage Rating Description

Nema Rating 5-20R

Logistics

Carton Quantity 10

Product Assets

Catalog Page - BRY B-9 Catalog Page Catalog Page - BRY D-2 Catalog Page Catalogs - Bryant Full Line Catalog

Literature - General Literature - Duplex Surge Receptacles Literature - General Literature - Surge Protection Devices

