



# Locking Devices, Isolated Ground Industrial, Flush Receptacle, 20A 125V, 2-Pole 3-Wire Grounding, L5-20R, Screw Terminal, Black

By Bryant  
Catalog # 70520IG



Locking Devices, Isolated Ground, Industrial, Nylon Flush Receptacle, 20A 125V, 2-Pole 3-Wire Grounding, L5-20R, Screw Terminal, Orange

### Features

- Limits electrical noise on the equipment grounding circuit by providing two grounding paths for the installation
- Nylon deep face design
- Triple-wipe brass line contacts
- Ground contacts and ground termination
- Nickel and brass plated wrap-around steel yoke

### Application

Extra Heavy Duty Industrial Specification Grade

### General

Catalog Number	70520IG
EU RoHS Indicator	Yes
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Item Type	20A Single Nylon Receptacle
Material	Composite
Material - Mounting Hardware	Screw Mounting
Number Of Poles	2-Pole
Series	Locking
Style	Isolated Ground
Type	Single Receptacle
UPC	781786688551

### Dimensions

Dimensions	3.28 in x 1.70 in x 1.24 in
Display Size	Standard Sized Product

Height	1.24 in
Length	3.28 in
Width	1.7 in

### Electrical Ratings

Amperage Rating	20 A
Connectivity	Terminal Screws
Current Rating	20 A
Phase	Single Phase
Voltage Rating	125 V
Voltage Rating Description	125V

### Conductor Related

Number Of Wires	3-Wire
Wire Size	#14 AWG to #8 AWG

### Certifications And Compliance

Nema Rating	L5-20R
Standards - RoHS Compliance	CM
Status	

### Logistics

Carton Quantity	10
-----------------	----

### Product Assets

- [Catalogs - Bryant Full Line Catalog](#)  
[Specifications - 70520IG Specification Sheet French](#)  
[Specifications - 70520IG Specification Sheet English](#)



A Hubbell brand