BRYANT®

Circuit Watch Surge Suppression Straight Blade Receptacle, Hospital Grade, 15A 125V, 2-Pole 3-Wire Grounding, 5-15R, Gray

By Bryant Catalog # SP82GYA

Circuit Watch Surge Suppression Straight Blade Receptacle, Hospital Grade, 15A 125V, 2-Pole 3-Wire Grounding, 5-15R, Gray.



General

Application Duplex with Light and Alarm

Catalog Number SP82GYA

Color

EU RoHS Indicator No

Environmental Conditions Indoor Dry Unless Protected By

Additional Means

Indicator(s) Type LED and Audible Alarm
Item Type Surge Protection Receptacles

Material Composite

Material - Mounting Hardware Mounting Screws

Operating Temperature 32 Deg F to 140 Deg F (O Deg

C to 60 Deg C)

Outlet Straight Blade

Response Time 5

Series Hospital Grade
Style Surge Protection Only
Type Duplex Receptacle
UPC 781786139251

Dimensions

Display Size Standard

Electrical Ratings

Amperage Rating 15 A

Connectivity Terminal Screws

Current / Amperage Rating 15 A
Current Rating 15 A
Frequency Rating 60 Hz
Phase Single Phase
Voltage Rating 125 V

Voltage Rating 125 V Voltage Rating Description 125 V

Certifications And Compliance

Nema Rating 5-15R

Logistics

Carton Quantity 10

Product Assets

Catalogs - Bryant Full Line Catalog

