



Locking Devices, Isolated Ground, Industrial, Flush Receptacle, 20A 125/250V, 3-Pole 4-Wire Grounding, L14-20R, Screw Terminal, Orange

By Bryant
Catalog # 71420IG



Locking Devices, Isolated Ground, Industrial, Flush Receptacle,
20A 125/250V AC, 3-Pole 4-Wire Grounding, L14-20R, Screw
Terminal, Orange

Application

Extra Heavy Duty Industrial Specification Grade

General

Catalog Number	71420IG
EU RoHS Indicator	Yes
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Item Type	20A Single Nylon Receptacle
Material	Composite
Material - Mounting Hardware	Screw Mounting
Number Of Poles	3-Pole
Series	Locking
Style	Isolated Ground
Type	Single Receptacle
UPC	781786695146

Dimensions

Dimensions	3.28 in x 1.70 in x 1.14 in
Display Size	Standard Sized Product
Height	1.14 in
Length	3.28 in
Width	1.7 in

Electrical Ratings

Amperage Rating	20 A
Connectivity	Terminal Screws
Current Rating	20 A
Phase	Single Phase
Voltage Rating	125/250 V
Voltage Rating Description	125/250V AC

Conductor Related

Number Of Wires	4-Wire
Wire Size	#14 AWG to #8 AWG

Certifications And Compliance

Nema Rating	L14-20R
Standards - RoHS Compliance Status	CM

Logistics

Carton Quantity	20
-----------------	----

Product Assets

[Catalogs - Bryant Full Line Catalog](#)
[Specifications - 71420IG](#)