BRYANT®

Locking Devices, Industrial, Flanged Inlet, 20A 3-Phase Delta 250V AC, 3-Pole 4-Wire Grounding, L15-20P, Screw Terminal, White

By Bryant Catalog # 71520MB

Locking Devices, Industrial, Flanged Inlet, 20A 3-Phase Delta 250V AC, 3-Pole 4-Wire Grounding, L15-20P, Screw Terminal, White

Application

Extra Heavy Duty Industrial

General

Catalog Number Color EU RoHS Indicator Environmental Conditions

Insulation Item Type Material Material - Mounting Hardware Number Of Poles Style Temperature Rating

Type UPC

Dimensions

Dimensions Display Size Height 71520MB White Yes Indoor Dry Unless Protected By Additional Means Insulated Body 20A Flanged Inlet Composite Screw Mounting 3-Pole Equipment Base Maximum Continuous: 75° C; Minimum Continuous: -40° C w/o impact Flanged Inlet 781786695863

3.06 in x 3.06 in x 2.03 in

Standard Sized Product

2.03 in



Length	3.06 in
Width	3.06 in

Electrical Ratings

Amperage Rating	20 A
Connectivity	Screw Terminals
Current Rating	20 A
Dielectric Strength	Withstands 3000V Minimum
Voltage Rating	3 Phase 250 VAC
Voltage Rating Description	3 Phase 250V AC

Conductor Related

Number Of Wires Wire Size 4-Wire #18 AWG to #8 AWG

Certifications And Compliance

Nema Rating

L15-20P

10

Logistics

Carton Quantity

Product Assets

Catalogs - Bryant Full Line Catalog Specifications - 71520MB

