BRYANT®

Locking Devices, Industrial, Female Connector Body, 20A 3-Phase Delta 480V AC, 3-Pole 4-Wire Grounding, L16-20R, Screw Terminal, Black and White

20A 480V 30
HEMA
(16-20)

By Bryant Catalog # 71620NC

Locking Devices, Industrial, Female Nylon Connector Body, 20A 3-Phase Delta 480V AC, 3-Pole 4-Wire Grounding, L16-20R, Screw Terminal, Black and White

Application

Heavy Duty Industrial

General

Catalog Number 71620NC
Color Black, White

EU RoHS Indicator Yes

Environmental Conditions Indoor Dry Unless Protected By

Additional Means

Insulation Insulated Body

Item Type 20A Triple Gripper Nylon

Connector

Material Composite

Material - Mounting Hardware Cord Mounted

Number Of Poles 3-Pole

Style Internal Cord Clamp

Temperature Rating Maximum Continuous: 75° C;

Minimum Continuous: -40° C w/o impact, -25° with impact.

Type Connector Body UPC 781786696891

Dimensions

Display Size Standard Sized Product

Height 3.9 in Length 2.13 in

Electrical Ratings

Amperage Rating 20 A

Connectivity Screw Terminals

Current Rating 20 A

Voltage Rating 3 Phase 480 VAC Voltage Rating Description 3 Phase 480 VAC

Conductor Related

Conductor Range #14 AWG to #12 AWG

Number Of Wires 4-Wire

Number of Conductors 4-Wire Grounding
Wire Size #18 AWG to #8 AWG

Certifications And Compliance

Nema Rating L16-20R Standards - RoHS Compliance CM

Status

Logistics

Carton Quantity 10
Pallet Quantity 2000

Product Assets

Catalogs - Bryant Full Line Catalog

Specifications - 71620NC