



# BIBD2/06

by Burndy Catalog ID: BIBD2/06

Prop65

Aluminum Multiple Tap Connector, Clear Insulated, 6 Port, 2 Sided Entry, 14-2/0 AWG, Al/Cu Rated.

Clear Plastisol covered AL6061-T6 aluminum body, Clear Plastisol

# **Product Details**

General	
Application	For Indoor Use Only, Copper Or Stranded Aluminum
Нех Кеу	3/16
Insulation	Υ
Insulation Type	Plastisol
Item Type	3B
Material	Aluminum
Material - Hardware	Aluminum
Number Of Ports	6
Physical Attribute - Number of Screws	6
Physical Attribute - Screw Type	Allen
Plated	Ν
Plating Type	Unplated
Sub Brand	UNITAP
Temperature Rating	194
Trade Name	UNITAP™
Туре	BIBD, Multi-Port
UPC	781810223970
UPC 12 Digit	7818102239700

#### Dimensions

Dimension - Height fraction	1.375 in
Dimension - Height inch	1.38 in
Dimension - L Length Overall mm	107 mm
Dimension - Length Overall inch	4.20 in
Dimension - Width fraction	1-14/25 in
Dimension - Width inch	1.56 in
Dimension - Width mm	40 mm

### **Electrical Ratings**

	Rating - Minimum Voltage	600
--	--------------------------	-----

Conductor - AL Str Size	8 AWG;6 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG;2/0 AWG
Conductor - AL Str Size Range	8 AWG-2/0 AWG
Conductor - Copper Str Size	14 AWG;12 AWG;10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 ;2/0 Str
Conductor - Copper Str Size Range	14 AWG-2/0 Str
Conductor Type	<ul><li>AL C Str-Size</li><li>CU C Str-Size</li></ul>

# Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Listed Direct Burial	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL468A-468B
Standards - Industry Standards Met	UL468A-468B
Standards - RoHS Compliance Status	СМ
UL Listed	Yes

1

# Logistics

Minimum Pack Quantity

# For further technical assistance, please contact us

#### **BURNDY Headquarters**

47 East Industrial Park Drive Manchester, New Hampshire 03109

#### Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday Emergency Service 24-hours/365 Days Phone: 1-800-346-4175 1-603-647-5299 (International)