



FD675D8TN

by Burndy Catalog ID: FD675D8TN

Prop 65 Notice

Copper Stud Connectors

Product Details

General

Application	Substation
Connector Type	Stud Connector
Material	Copper Alloy
Material - Hardware	DURIUM™ Silicon Bronze
Physical Attribute - Number of Holes	4
Physical Attribute - Pad Configuration	4x4 - 4 holes
Physical Attribute - Pad Orientation	In-line
Plated	Y
Plating Type	Tin - Electro Plated
Туре	Studs
UPC	781810289839
UPC 12 Digit	7818102898399

Dimensions

Dimension - B Length inch	2.18 in
Dimension - Bolt Size fraction	1/2
Dimension - D inch	4.00 in
Dimension - F Width Center to Center inch	1.75 in
Dimension - L Length Overall mm	188 mm
Dimension - Length Overall inch	7.39 in
Dimension - N inch	1.12 in
Dimension - Pad Width inch	4.00 in
Dimension - Pin Diameter fraction	1-3/4 in
Dimension - Pin Diameter inch	1.750 in
Dimension - Thread Size	1/2-12
Dimension - Threads per inch	12

Electrical Ratings

Rating - KVA	230 kV	
Ruling RVA	250 KV	

Conductor Related

Certifications and Compliance		
Certification - CSA Approved	No	
Certification - ETL	No	
Certification - UL Recognized	No	
Certification - cULus	No	
Standards - RoHS Compliance Status	EX	
UL Listed	No	

Stud to Pad

Logistics

	Minimum Pack Quantity	1		

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive Manchester, New Hampshire 03109

Conductor - Connection Combination

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday Emergency Service 24-hours/365 Days Phone: 1-800-346-4175 1-603-647-5299 (International)