



KPA4CUP

by Burndy Catalog ID: KPA4CUP

Prop 65 Notice

Copper Alloy Scrulug, 14 Sol. - 4 Str., 1.28 in L, .50 in W, CU Finish.

Features: High Copper Alloy Terminal For Joining A Wide Range Of Cable To Equipment Pads Or Terminal Blocks, One Piece Design, Superior Torque And Pull Out Performance, Convenient Range Taking Design, Reduces Catalog Numbers, One Catalog Number Accommodates Several Conductor Sizes, High Conductivity Copper Alloy, Long Lasting, Reliable Contact, Compact Design, Easy To Use, Slot Robertson Screw, Hex Head, Hex Socket Bolt, No Special Installation Tools Required, Eliminates Over-Torquing/Potential Conductor Damage, Dimension T: 07 IN, Dimension D: 0.71 IN, Stud/bolt Hole Size: 1/4 IN, Dimension K: 0.28 IN, Dimension N: 0.33 IN, Set Screw Type: Slot Robertson, Tongue Width: 0.5 IN, Length: 1.28 IN, Height: 1 IN, Installation Torque: 45 IN-LB

Product Details

General

Application	For Joining A Wide Range Of Copper Cable To Equipment Pads Or Terminal Blocks
Connector Type	Terminal
Hardware Type	5/16 DIA.SLOT ROBERTSON
Installation Torque Recommended in-Ib	45 LBS/in
Material	Copper
Physical Attribute - Number of Holes	1
Physical Attribute - Number of Screws	1
Physical Attribute - Screw Type	Slot
Plated	Ν
Plating Type	Unplated
Sub Brand	SCRULUG
Trade Name	SCRULUG™
Туре	Bolted Lugs & Terminals
UPC	781810354360

Dimensions

Dimension - D inch	0.71 in
Dimension - Height fraction	1 in
Dimension - Height inch	1.00 in
Dimension - Hole Size inch	0.28 in
Dimension - Hole Size mm	7 mm
Dimension - L Length Overall mm	33 mm
Dimension - Length Overall inch	1.28 in
Dimension - N inch	0.33 in
Dimension - Pad Width inch	0.50 in

Dimension - Strip Length inch	9/16
Dimension - Stud Size inch	1/4

Conductor Related

Conductor - Copper Solid Size	14;13;12;11;10;9;8;7;6;5;4
Conductor - Copper Solid Size Range	14-4
Conductor - Copper Str Size	14;12;10;9;8;7;6;5;4
Conductor - Copper Str Size Range	14-4
Conductor Type	CU C Str-SizeCU C Solid-Size

Certifications and Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	СМ
UL Listed	Yes

1

Logistics

Minimum Pack Quantity

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive Manchester, New Hampshire 03109 Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday Emergency Service 24-hours/365 Days Phone: 1-800-346-4175 1-603-647-5299 (International)