



KPA8CUP

by Burndy Catalog ID: KPA8CUP

Prop 65 Notice

Copper Terminal, 1 Hole, 14 AWG (Sol)-6 AWG (Str), #10 Stud, 1 Screw.

Features: High Copper Alloy Terminal For Joining A Wide Range Of Cable To Equipment Pads Or Terminal Blocks, One Piece Design, Superior Torque And Pull Out Performance, Convenient Range Taking Design, Reduces Catalog Numbers, One Catalog Number Accommodates Several Conductor Sizes, High Conductivity Copper Alloy, Long Lasting, Reliable Contact, Compact Design, Easy To Use, Slot Robertson Screw, Hex Head, Hex Socket Bolt, No Special Installation Tools Required, Eliminates OverTorquing/Potential Conductor Damage, Stud/bolt Hole Size: #10, Dimension T: 07 IN, Dimension D: 0.51 IN, Dimension N: 0.24 IN, Dimension K: 0.2 IN, Set Screw Type: Slot Robertson, Tongue Width: 0.38 IN, Installation Torque: 35 IN-LB, Height: 0.81 IN, Length: 11 IN

Product Details

General

| Application | For Joining A Wide Range Of Copper Cable To Equipment Pads Or Terminal Blocks |
|---------------------------------------|---|
| Connector Type | Terminal |
| Hardware Type | # 12-24 SLOT |
| Installation Torque Recommended in-lb | 35 |
| Material | Copper |
| Physical Attribute - Number of Holes | 1 |
| Physical Attribute - Number of Screws | 1 |
| Physical Attribute - Screw Type | Slot |
| Plated | N |
| Plating Type | Unplated |
| Sub Brand | SCRULUG |
| Trade Name | SCRULUG™ |
| Туре | Bolted Lugs & Terminals |
| UPC | 781810354353 |

Dimensions

| Dimension - D inch | 0.56 in |
|---------------------------------|----------|
| Dimension - Height fraction | 64/79 in |
| Dimension - Height inch | 0.81 in |
| Dimension - Hole Size inch | 0.20 in |
| Dimension - Hole Size mm | 5 mm |
| Dimension - L Length Overall mm | 26 mm |
| Dimension - Length Overall inch | 1.04 in |
| Dimension - N inch | 0.22 in |
| Dimension - Pad Width inch | 0.38 in |

| Dimension - Strip Length inch | 15/32 |
|-------------------------------|---------|
| Dimension - Stud Size inch | #10 |
| Dimension - Width inch | 0.38 in |
| Dimension - Width mm | 10 mm |

Conductor Related

| Conductor - Copper Solid Size | 14 AWG;13 AWG;12 AWG;11 AWG;10 AWG;9 AWG;8 AWG;7 AWG;6 AWG |
|-------------------------------------|--|
| Conductor - Copper Solid Size Range | 14 AWG-6 AWG |
| Conductor - Copper Str Size | 14 AWG;12 AWG;10 AWG;9 AWG;8 AWG;7 AWG;6 AWG |
| Conductor - Copper Str Size Range | 14 AWG-6 AWG |
| Conductor Type | CU C Str-Size CU C Solid-Size |

Certifications and Compliance

| Certification - CSA Approved | Yes |
|------------------------------------|--------------|
| Certification - ETL | No |
| Certification - UL Recognized | No |
| Certification - cULus | No |
| Industry Standard(s) | UL 486A-486B |
| Standards - Industry Standards Met | UL 486A-486B |
| Standards - RoHS Compliance Status | СМ |
| UL Listed | Yes |

Logistics

| Minimum Pack Quantity | 1 |
|-----------------------|---|
|-----------------------|---|

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday Emergency Service 24-hours/365 Days

Phone: 1-800-346-4175

1-603-647-5299 (International)