

QQA442N

by Burndy
Catalog ID: QQA442N

Prop 65 Notice

Copper Terminal, Heavy Duty, 2 Hole, 850-1000 kcmil, 1/2" Stud, 1-3/4" Stud Hole Spacing, 2 Screws



Product Details

General

Connector Type	Terminal
Installation Torque Recommended in-lb	500 LBS/in
Material	Copper
Physical Attribute - Number of Holes	2
Physical Attribute - Number of Screws	2
Physical Attribute - Screw Type	Hexagonal Bolt
Plated	N
Plating Type	Unplated
Trade Name	QIKLUG™
Type	Bolted Lugs & Terminals
UPC	781810006122

Dimensions

Dimension - D inch	3.00 in
Dimension - F Width Center to Center inch	1.75 in
Dimension - Height fraction	2.5 in
Dimension - Height inch	2.50 in
Dimension - Hole Size inch	0.56 in
Dimension - Hole Size mm	14 mm
Dimension - L Length Overall mm	179 mm
Dimension - Length Overall inch	7.06 in
Dimension - N inch	0.63 in
Dimension - Pad Width inch	1.88 in

Conductor Related

Conductor - Copper Str Navy Size	1000 (127) Navy
Conductor - Copper Str Navy Size Range	1000 (127) Navy
Conductor - Copper Str Size	900 kcmil;1000 kcmil
Conductor - Copper Str Size Range	900 kcmil-1000 kcmil
Conductor Type	<ul style="list-style-type: none"> • CU C Str-Size • CU C Str Navy-Size

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	EX
UL Listed	Yes

Logistics

Minimum Pack Quantity	2
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)