



TP1410BF

by Burndy Catalog ID: TP1410BF

Block Fork (Brazed Seam), 16 AWG - 14 AWG, 8-10, .95 in L, Wire strip length:13/64.

Features: VINYLUG Type TP Is Designed For Commercial And Light Duty Industrial Control And Power Circuit Applications, Supplied With An Expanded Polyvinyl Chloride (PVC) Insulation Shroud, Many Tongue Variations And Rated 600 V Makes TP Terminals Versatile And Economical, Expanded Insulation Support Accepts Standard And Large Wire Diameters, Lowers Inventory Requirements, Permits Greater Flexibility And Provides Insulation Support, Funnel Entry: Easy Wire Insertion, Manufactured Of Pure Electrolytic Copper: Provides Maximum Conductivity, Low Resistance And Ductility For Excellent Crimp Forming Properties, Deep V Groove Serrations In The Inner Barrel: Provides Added Holding Strength And Better Conductivity Electro-Tin Plated: Provides Durable Long-Lasting Corrosion Resistance, 600 V Maximum, 105 DEG C Maximum, Insulation Diameter (maximum): 0.18 IN, Wire Strip Length: 13/64 IN, Color Code: Blue, Temperature Rating: 105 DEG C Maximum, Finish: Electro-Tin Plated

Product Details

General

| Application | For Commercial And Light Duty Industrial Control And Power Circuit Applications |
|----------------------------------|---|
| Connector Type | Terminal |
| Feature - Barrel Style | Shrouded |
| Insulation | Y |
| Insulation Type | Vinyl |
| Material | Copper |
| Physical Attribute - Tongue Type | Block Fork |
| Plated | Y |
| Plating Type | Tin |
| Sub Brand | HYDENT |
| Trade Name | INSULUG™ |
| Туре | Fork Tongue |
| UPC | 781810524336 |
| UPC 12 Digit | 7818105243366 |

Dimensions

| Cable Insulation Diameter Maximum | 0.180 in |
|-----------------------------------|----------|
| Dimension - L Length Overall mm | 24 mm |
| Dimension - Length Overall inch | 0.95 in |
| Dimension - Pad Width inch | 0.32 in |
| Dimension - Strip Length inch | 13/64 in |
| Dimension - Stud Size inch | #8 - #10 |
| Dimension - Z inch | 0.30 in |

Conductor Related

| Conductor Range | #16 AWG to #14 AWG |
|-----------------|---|
| Conductor Type | CU C Solid-SizeCU C Str-Size |

Certifications and Compliance

| Certification - CSA Approved | No |
|------------------------------------|----|
| Certification - ETL | No |
| Certification - UL Recognized | No |
| Certification - cULus | No |
| Standards - RoHS Compliance Status | СМ |
| UL Listed | No |

Logistics

| Carton Quantity | 100 EA |
|-----------------------|--------|
| Minimum Pack Quantity | 100 |

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday Emergency Service 24-hours/365 Days

Phone: 1-800-346-4175

1-603-647-5299 (International)