



YA6C2TC38E2

by Burndy Catalog ID: YA6C2TC38E2

Prop 65 Notice

Cu Comp Terminal Code Cond, Bvl Entry, 2 Hole/W/O/InspWindow, #6 AWG Code, 30 Navy, 600 V-35 kV, 3/8" Stud, 0.75" Spacing, Lng bbl, Blue, 7 or 374 Index.

Features: UL Listed 90 DEG C, 600 V - 35 KV, 45 DEG And 90 DEG Angles Are Available, Tongue Angle: Straight, Wire Strip Length: 1-3/16 IN, Temperature Rating: 90 DEG C, Finish: Electro-Tin Plated, Color Code: Blue, Tools, Die Set Catalog Number, And (number Of Crimps): Mechanical: MD6, OUR840, MD7-34R Tool, W5CVT, W5CRT, X5CRT, X8CART Die, (2), Hydraulic: BCT500HS, Y500CTHS Tool, W5CVT, W5CRT, X5CRT, X8CART Die, (2), Y35, Y39, Y750, Y46, PAT750 Tool, U5CRT, U8CABT Die, (2), Y46 Tool, U5CRT, U8CABT Die With PUADP-1 Adapter, (2), Dieless Tools (number Of Crimps): Y81KFT, Y81KFTMBH, PAT81KFT-18V Tool, (1), Y1MRTC, MY29-3, MY29-11, MRC840 Tool, (2), Die Index: 7

Product Details

General

Application	For Code Conductor		
Color Code	Blue Terminal		
Connector Type			
Die Index	7;374		
Feature - Barrel Style	Chamfered		
Feature - Barrel Type	Long Copper 2		
Material			
Physical Attribute - Number of Holes			
Physical Attribute - Tongue Type	Straight Y Tin HYLUG HYLUG [™] Long Barrel, Tin Plated 781810174616		
Plated			
Plating Type			
Sub Brand			
Trade Name			
Туре			
UPC			
UPC 12 Digit	7818101746166		

Dimensions

Dimension - B Length inch	1.12
Dimension - Bolt Hole Size inch	0.41
Dimension - Hole Size inch	0.41
Dimension - Hole Size mm	10
Dimension - L Length Overall mm	75
Dimension - Length Overall inch	2.97
Dimension - N inch	0.41
Dimension - Outside Diameter inch	0.29

Dimension - Pad Width inch	0.58
Dimension - Strip Length inch	1-3/16 in
Dimension - Stud Size inch	3/8 in
Dimension - Z inch	0.43 in
Physical Attribute - Tongue Angle	Straight

Electrical Ratings

Rating - KVA		35 kV
Rating - Minimum V	oltage	600
Voltage - Maximum		35000

Conductor Related

Conductor - Copper Solid Size	6 AWG
Conductor - Copper Str Navy Size	30 (19) Navy
Conductor - Copper Str Navy Size Range	30 (19) Navy
Conductor - Copper Str Size	6 AWG
Conductor - Material	Copper

Certifications and Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	СМ
UL Listed	Yes

Logistics

	Minimum Pack Quantity	I		

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday Emergency Service 24-hours/365 Days Phone: 1-800-346-4175 1-603-647-5299 (International)