

YTW52RT521REKHT

by Burndy
Catalog ID: YTW52RT521REKHT

Full Tension, ACSS EHV Deadend Kits, Hardware TMH9, 1192.5 (45/7) kcmil-1351.5 (45/7) kcmil, YTW52RT521REKHTNT Aluminum Dead End Assy., BYNA52RT15HHT Terminal



Product Details

General

Application	For 250 Deg C. rated ACSS transmission lines, Corona free operation up to 230 KV
Connector Type	Deadend
Physical Attribute - Number of Holes	4
Prefilled Oxide Inhibitor	N
UPC	781810222041
UPC 12 Digit	7818102220411

Dimensions

Dimension - B Length inch	2.69 in
Dimension - Hole Size inch	1.25 in
Dimension - Length Overall inch	35.55 in
Dimension - Pad Width inch	4.00 in
Dimension - Width inch	1.00 in

Electrical Ratings

Voltage - Maximum	230 kV
-------------------	--------

Conductor Related

Conductor - ACSS Str Size	1192.5 (45/7) kcmil;1192.5 (48/7) kcmil;1192.5 (54/19) kcmil;1272 (42/7) kcmil;1272 (45/7) kcmil;1272 (48/7) kcmil;1272 (54/19) kcmil;1351.5 (42/7) kcmil;1351.5 (45/7) kcmil
Conductor - ACSS Str Size Range	1192.5 (45/7) kcmil-1351.5 (45/7) kcmil
Conductor - Material	Aluminum

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	UI
UL Listed	No

Logistics

Minimum Pack Quantity

1

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)