



SPOOL INSULATOR SECONDARY CLEVIS

By CHANCE Utility
Catalog # [0337](#)

Clevis bracket for spool insulators used in secondary line deadend applications. Minimum ultimate deadend strength is 4,000 lbs. Used with ANSI Class 53-2 or 53-3 spool insulators. Replacement components: clevis pin - 450033P; cotter pin - 056747P.



Features

- 11/16" x 1-1/8" mounting hole
- 5/8" dia. clevis pin with self-locking cotter pin
- Hot dip galvanized per ASTM A-153
- Manufactured in compliance with ANSI/IEEE C135.20

General

Coating	Galvanized, ASTM A-153
Material	Steel
Type	Insulated Secondary Clevis
UPC	096359066835

Dimensions

Distance From Pole	N/A
Height	3.25 in
Length	4.00 in
Weight	2.45 lb

Certifications and Compliance

Industry Standard(s)	ANSI C135.20
----------------------	--------------

Logistics

Pallet Quantity	720
-----------------	-----

Product Assets

[Catalogs - Pole Line Hardware](#)
[Sales Drawings - Insulator Clevis \(SA0337\)](#)

Related Products

[C9091032P - INSULATOR, SPOOL, ANSI 53-2 CLASS, POLYMER, BLACK](#)
[C9091034 - PORCELAIN SPOOL INSULATOR, ANSI 53-4, GRAY](#)
[DE4S5 - PORCELAIN SPOOL INSULATOR, ANSI 53-2, GRAY](#)



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.
CH-0337-SPEC-EN | REV 7/2023