



# SPOOL INSULATOR SECONDARY CLEVIS

By Chance  
Catalog # 0338

Clevis bracket for spool insulators used in secondary line deadend applications. Minimum ultimate deadend strength is 4,000 lbs. Used with ANSI Class 53-2 or 53-3 spool insulators. Replacement components: clevis pin - 450033P; cotter pin - 056747P.

## Features

- 11/16" x 1-1/8" mounting hole
- 5/8" dia. clevis pin with self-locking cotter pin
- Hot dip galvanized per ASTM A-153
- Manufactured in compliance with ANSI/IEEE C135.20

## General

|                |                            |
|----------------|----------------------------|
| Catalog Number | 0338                       |
| Coating        | Galvanized, ASTM A-153     |
| Material       | Steel                      |
| Type           | Insulated Secondary Clevis |
| UPC            | 096359066842               |

## Dimensions



|                    |                               |
|--------------------|-------------------------------|
| Dimensions         | 5.000 in x 4.375 in x 3.25 in |
| Distance From Pole | N/A                           |
| Height             | 3.25 in                       |
| Length             | 5 in                          |
| Weight             | 2.11 lb                       |
| Width              | 4.375 in                      |

## Logistics

|                 |     |
|-----------------|-----|
| Pallet Quantity | 640 |
|-----------------|-----|

## Product Assets

- [Catalogs - Pole Line Hardware](#)
- [Sales Drawings - Insulator Clevis](#)
- [Specifications - 338](#)