



SPOOL INSULATOR SECONDARY DEADEND CLEVIS w/GRAY ANSI 53-1 INSULATOR

By Chance
Catalog # [0341G531](#)



Clevis bracket for spool insulators used in secondary deadend applications. Deadend strength is 2,000 lbs. Used with ANSI Class 53-1 spool insulators. Replacement components: clevis pin - 450026P; cotter pin - 056747P.

Features

- 3/16" x 1-1/2" material
- 11/16" x 3/4" dia. mounting hole
- 1/2" dia.clevis pin with self-locking cotter pin
- Hot dip galvanized per ASTM A-153
- Manufactured in compliance with ANSI/IEEE C135.20, item 1

General

Catalog Number	0341G531
Coating	Galvanized, ASTM A-153
EU RoHS Indicator	No
Material	Steel
Type	Insulated Secondary Clevis
UPC	096359266907

Dimensions

Dimensions	5.000 in x 3.625 in x 2.38 in
Distance From Pole	N/A
Height	2.38 in
Length	5 in
Weight	2.04 lb
Width	3.625 in

Certifications And Compliance

Buy America(n) Qualified	Contact Manufacturer
--------------------------	----------------------

Logistics

Pallet Quantity	432
-----------------	-----

Product Assets

- [Catalogs - Pole Line Hardware](#)
- [Sales Drawings - Service Dead-End Clevis](#)
- [Specifications - 0341G531](#)



A Hubbell brand