



SPOOL INSULATOR DEADEND CLEVIS, SWINGING STYLE

By CHANCE Utility
Catalog # [0352](#)

Clevis bracket for spool insulators used in secondary deadend applications attaches to ovaleye bolt. Minimum ultimate deadend strength is 4,000 lbs. Used with ANSI Class 53-2 or 53-3 spool insulators. Replacement components: clevis pin - 450033P; cotter pin - 056747P.



Features

- 5/8" dia. clevis pin with self-locking cotter pin
- Hot dip galvanized per ASTM A-153
- Manufactured in compliance with ANSI/IEEE C135.20

General

Coating	Galvanized, ASTM A-153
Material	Steel
Type	Insulated Secondary Clevis
UPC	096359066903

Dimensions

Distance From Pole	N/A
Height	3.25 in
Length	5.00 in
Weight	1.52 lb

Certifications and Compliance

RUS Listed Reference s - Clevis, secondary swinging

Logistics

Pallet Quantity 960

Product Assets

[Catalogs - Pole Line Hardware](#)
[Sales Drawings - Swinging Clevis \(SA0352\)](#)

Related Products

[DE4S5 - PORCELAIN SPOOL INSULATOR, ANSI 53-2, GRAY](#)
[C9091032P - INSULATOR, SPOOL, ANSI 53-2 CLASS, POLYMER, BLACK](#)
[C9091034 - PORCELAIN SPOOL INSULATOR, ANSI 53-4, GRAY](#)



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.
CH-0352-SPEC-EN | REV 7/2023