



## CROSSARM INSULATOR PIN with 1in NYLON THREAD, CLAMP TYPE STYLE

By CHANCE Utility  
Catalog # [14322P](#)

Insulator pin used to support pin type insulator with 1" NEMA internal thread on crossarm.



\*Representative Image

### Features

- Includes two 5/8" x 7" carriage bolts, two square nuts, two curved lock nuts and a 5/16" x 1-1/2" washer plate
- Cantilever load rating is 1,500 lbs. based on ANSI/IEEE 10 degree deflection criteria
- Hot dip galvanized per ASTM A-153
- RUS Listed, f - Pin, crossarm

### General

Coating	Galvanized, ASTM A-153
Material	Steel
Type	Pins
UPC	096359398264

### Dimensions

Distance From Pole	N/A
Length - Threaded Area	3
Weight	5.3 lb

### Certifications and Compliance

RUS Listed Reference	f - Pin, crossarm
----------------------	-------------------

### Logistics

Pallet Quantity	192
-----------------	-----

### Product Assets

[Catalogs - Pole Line Hardware Supplements \(5-53Supp1-19\)](#)  
[Installation Manuals - CHANCE® Nylon Thread Insulator Pin Instructions](#)  
[Sales Drawings - Straight Corner Pin \(SA14322P\)](#)



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.  
CH-14322P-SPEC-EN | REV 7/2023