



SPOOL INSULATOR DEADEND CLEVIS, SWINGING STYLE

By Chance
Catalog # 1948C



Clevis bracket for spool insulators used in secondary deadend applications. Minimum ultimate deadend strength is 2,000 lbs. Used with ANSI Class 53-1 spool insulators. Replacement components: clevis pin - P2070061; cotter pin - 056746P.

Features

- 23/64" dia. clevis pin with self-locking cotter pin
- Hot dip galvanized per ASTM A-153
- Manufactured in compliance with ANSI/IEEE C135.20

General

Catalog Number	1948C
Coating	Galvanized, ASTM A-153
Material	Steel
Style	Clevis Only (less mounting bracket)
Type	Insulated Secondary Clevis
UPC	096359068969

Dimensions

Dimensions	3.625 in x 3.375 in x 2.25 in
------------	-------------------------------

Distance From Pole	N/A
Height	2.25 in
Length	3.625 in
Weight	0.4 lb
Width	3.375 in

Certifications And Compliance

RUS Listed Reference	as - Clevis, service swinging
----------------------	-------------------------------

Logistics

Pallet Quantity	4000
-----------------	------

Product Assets

- [Catalogs - Pole Line Hardware](#)
- [Sales Drawings - Clevis Swinging Service](#)
- [Specifications - 1948C](#)



A Hubbell brand