



# SPOOL INSULATOR DEADEND CLEVIS, SWINGING STYLE w/MOUNTING BRACKET

By CHANCE Utility  
Catalog # 1948M

Clevis bracket for spool insulators used in secondary deadend applications. Minimum ultimate deadend strength is 2,000 lbs. Used with ANSI Class 53-1 spool insulators. Includes angle bracket with 11/16" hole. Replacement components: clevis pin - P2070061; cotter pin - 056746P.



## Features

- 23/64" dia. clevis pin with self-locking cotter pin
- Hot dip galvanized per ASTM A-153
- Bracket has 5/8" dia. hole for mounting
- Manufactured in compliance with ANSI/IEEE C135.20

## General

Coating	Galvanized, ASTM A-153
Material	Steel
Style	Clevis & Mounting Bracket
Type	Insulated Secondary Clevis
UPC	096359236009

## Dimensions

Distance From Pole	N/A
Height	2.25 in
Length	2.50 in
Weight	0.65 lb

## Logistics

Pallet Quantity	2160
-----------------	------

## Product Assets

[Catalogs - Pole Line Hardware](#)  
[Sales Drawings - Clevis Swinging Service \(SA1948C\)](#)



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.  
CH-1948M-SPEC-EN | REV 7/2023