



# SPOOL INSULATOR SECONDARY DEADEND CLEVIS

By Chance  
Catalog # 468

Clevis bracket for spool insulators used in secondary deadend applications. Deadend strength is 3,000 lbs. Used with ANSI Class 53-2 spool insulators. Replacement components: clevis pin - 450036P; cotter pin - 056747P.

## Features

- 1" x 1/2" x 1/8" channel material
- 11/16" square mounting hole
- 5/8" dia. x 4-3/4" clevis pin with self-locking cotter pin
- Hot dip galvanized per ASTM A-153
- Manufactured in compliance with ANSI/IEEE C135.20, item 3

## General

Catalog Number	468
Coating	Galvanized, ASTM A-153
Material	Steel
Type	Insulated Secondary Clevis
UPC	096359072041

## Dimensions

Dimensions	5.500 in x 1.000 in x 5.000 in
Distance From Pole	N/A



Height	5 in
Length	5.5 in
Weight	1.33 lb
Width	1 in

## Certifications And Compliance

Industry Standard(s)	ANSI C135.20
----------------------	--------------

## Logistics

Pallet Quantity	1200
-----------------	------

## Product Assets

- [360 Product View - CHAN\\_468](#)
- [3D Product View - CHAN\\_468](#)
- [Catalogs - Pole Line Hardware](#)
- [Sales Drawings - Insulated Clevis](#)
- [Specifications - 468](#)



A Hubbell brand