



# SPOOL INSULATOR SECONDARY DEADEND CLEVIS

By Chance  
Catalog # 469



Clevis bracket for spool insulators used in secondary deadend applications. Minimum ultimate deadend strength is 4,000 lbs. Used with ANSI Class 53-2 and 53-3 spool insulators. Replacement components: clevis pin - 450033P; cotter pin - 056747P.

### Features

- 1-1/2" x 1/2" x 1/8" channel material
- 11/16" x 7/8" dia. mounting hole with retainer tabs that captures the bolt head and resist rotation
- 5/8" dia. clevis pin with self-locking cotter pin
- Hot dip galvanized per ASTM A-153
- Manufactured in compliance with ANSI/IEEE C135.20, item 4

### General

Catalog Number	469
Coating	Galvanized, ASTM A-153
Material	Steel
Type	Insulated Secondary Clevis
UPC	096359072058

### Dimensions

Dimensions	5.000 in x 1.500 in x 5.250 in
Distance From Pole	N/A
Height	5.25 in
Length	5 in
Weight	1.56 lb
Width	1.5 in

### Logistics

Pallet Quantity	960
-----------------	-----

### Product Assets

- [Catalogs - Pole Line Hardware](#)
- [Sales Drawings - Insulated Clevis](#)
- [Specifications - 469](#)



A Hubbell brand