



**PULLING-IN IRON, 12in LENGTH x
10-7/8in WIDTH, 7/8in STEEL ROD
SIZE, 20,000lbs MINIMUM
ULTIMATE TENSILE**

By Chance
Catalog # [8120](#)

Pulling-in irons are set into the brick or concrete walls of street vaults opposite all duct entrances. Provides a strong attachment for the pulling-in blocks when installing or removing cable

Features

- Galvanized per ASTM A-153
- in compliance with CAO 4552 specification

General

| | |
|----------------|------------------------|
| Catalog Number | 8120 |
| Coating | Galvanized, ASTM A-153 |
| Material | Steel |
| UPC | 096359074809 |

Dimensions

| | |
|--------------------|---------|
| Distance From Pole | N/A |
| Weight | 5.68 lb |

Certifications And Compliance



*Representative Image

Buy America(n) Qualified

- Buy America Compliant (All status valid till December 2025)
- Buy American Act Compliant (All status valid till December 2025)
- BABA Compliant (All status valid till December 2025)

Logistics

| | |
|-----------------|-----|
| Pallet Quantity | 250 |
|-----------------|-----|

Product Assets

[Sales Drawings - Pulling-In Iron](#)
[Specifications - 8120](#)



A Hubbell brand