



BOLT, DA, 5/8in x 12in, w/4 NUTS

By Chance
Catalog # [8862](#)



Double-arming bolts are used in pairs to "unitize" two crossarms when line construction requires the strength of double arm construction. Industry slang is D A Bolt.

Features

- Full-thread with cone pointed ends
- Includes four square nuts
- Rated tensile strength is 12,400 lbs.
- Galvanized per ASTM A-153
- Manufactured in compliance with ANSI C135.1 and CAO 6645
- RUS listed, n, Bolt, double-arming

General

Catalog Number	8862
Coating	Galvanized, ASTM A-153
Material	Steel
Tensile Strength	12400 lb.
UPC	096359075677

Dimensions

Diameter	0.63 in
Diameter (Fraction)	5/8 in
Dimensions	12.625 in x 1.000 in x 1.000 in
Distance From Pole	N/A
Height	1 in
Length	12.625 in
Weight	1.24 lb
Width	1 in

Certifications And Compliance

Industry Standard(s)	ANSI C135.1
RUS Listed Reference	n - Bolt, double arming

Logistics

Pallet Quantity	960
-----------------	-----

Product Assets

- [Catalogs - Communications Catalog](#)
- [Catalogs - Machine Bolts & DA Bolts](#)
- [Sales Drawings - 5/8" Double Arming Bolt](#)



A Hubbell brand