



# BOLT, DA, 5/8in x 16in, w/4 NUTS

By Chance  
Catalog # [8866](#)



Double-arming bolts are used in pairs to "unitize" two crossarms when line constructin requires the strength of double arm construction. Industry slang is D A Bolt.

## Features

- Full-thread with cone pointed ends
- Includes four square nuts
- Rated tensile strength is 12,400 lbs.
- Galvanized per ASTM A-153
- Manufactured in compliance with ANSI C135.1 and CAO 6645
- RUS listed, n, Bolt, double-arming

## General

Catalog Number	8866
Coating	Galvanized, ASTM A-153
Material	Steel
Tensile Strength	12400 lb.
UPC	096359075691

## Dimensions

Diameter	0.63 in
Diameter (Fraction)	5/8 in

Dimensions	16.625 in x 1.000 in x 1.000 in
Distance From Pole	N/A
Height	1 in
Length	16.625 in
Weight	1.73 lb
Width	1 in

## Certifications And Compliance

Industry Standard(s)	ANSI C135.1
RUS Listed Reference	n - Bolt, double arming

## Logistics

Pallet Quantity	960
-----------------	-----

## Product Assets

[Catalogs - Communications Catalog](#)  
[Catalogs - Machine Bolts & DA Bolts](#)  
[Sales Drawings - 5/8" Double Arming Bolt](#)  
[Specifications - 8866](#)



A Hubbell brand