



BOLT, DA, 5/8in x 22in, w/4 NUTS

By CHANCE Utility
Catalog # [8872](#)



Double-arming bolts are used in pairs to "unitize" two crossarms when line construction requires the strength of double arm construction. Industry slang is D A Bolt.

Features

- Full-thread with cone pointed ends
- Includes four square nuts
- Rated tensile strength is 12,400 lbs.
- Galvanized per ASTM A-153
- Manufactured in compliance with ANSI C135.1 and CAO 6645
- RUS listed, n, Bolt, double-arming

General

| | |
|------------------|------------------------|
| Coating | Galvanized, ASTM A-153 |
| Material | Steel |
| Tensile Strength | 12400 lb |
| UPC | 096359075738 |

Dimensions

| | |
|---------------------|----------|
| Diameter | 0.63 in |
| Diameter (Fraction) | 5/8 in |
| Distance From Pole | N/A |
| Length | 22.00 in |
| Weight | 2.09 lb |

Certifications and Compliance

| | |
|----------------------|-------------------------|
| Industry Standard(s) | ANSI C135.1 |
| RUS Listed Reference | n - Bolt, double arming |

Logistics

| | |
|-----------------|-----|
| Pallet Quantity | 960 |
|-----------------|-----|

Product Assets

[Catalogs - Communications Catalog \(CA12042E\)](#)
[Catalogs - Machine Bolts & DA Bolts \(5-53Supp24-28\)](#)
[Sales Drawings - 5/8" Double Arming Bolt \(SA8862\)](#)

Related Products

[C2050186 - SPRING WASHER, REGULAR-DUTY DOUBLE-COIL, 5/8in SIZE](#)
[6813 - WASHER, SQ FLAT, 5/8in SIZE, 2 1/4in](#)
[3512 - MF TYPE CURVED LOCK NUT, 5/8in THREAD](#)
[6805 - WASHER, ROUND, 11/16in HOLE, 1 3/4in DIA.](#)



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.
CH-8872-SPEC-EN | REV 4/2023