



## BOLT, DA, 3/4in X 18in, LESS NUTS

By Hubbell  
Catalog # [8888NN](#)



Double-arming bolts are used in pairs to "unitize" two crossarms when line construction requires the strength of double arm construction. Industry slang is D A Bolt.

### Features

- Full-thread with cone pointed ends
- Rated tensile strength is 18,350 lbs.
- Galvanized per ASTM A-153
- Manufactured in compliance with ANSI C135.1 and CAO 6645
- RUS listed, n, Bolt, double-arming

### General

Coating	Galvanized, ASTM A-153
Material	Steel
Tensile Strength	18350 lb.
UPC	096359384892

### Dimensions

Diameter	0.75 in
Diameter (Fraction)	3/4 in
Length	18.00 in
Weight	2.25 lb

### Logistics

Pallet Quantity	900
-----------------	-----

### Product Assets

[Sales Drawings - Double Arm Bolt \(SA8860NN\)](#)

### Related Products

- [6823 - 3in SQUARE CURVED WASHER for 3/4in BOLT SIZE, 7/8in HOLE](#)
- [6814 - 2-1/4in SQUARE FLAT WASHER for 3/4in BOLT SIZE, 13/16in HOLE](#)
- [C2050187 - SPRING WASHER, REGULAR-DUTY DOUBLE-COIL, 3/4in SIZE](#)
- [3513 - MF TYPE CURVED LOCK NUT, 3/4in THREAD](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
CH-8888NN-SPEC-EN | REV 1/2024