



## SPOOL INSULATOR SECONDARY CLEVIS, SAGGER STYLE

By CHANCE Utility  
Catalog # [C2070116](#)

Clevis bracket for spool insulators used in secondary deadend applications. A 5/8" machine bolt functions as the clevis pin. When tightened into the threaded lower hole of the clevis, the square head of the bolt seats into the indent of the clevis to lock in place. Note: clevis pin and cotter pin are not supplied with this style of clevis. For use with ANSI Class 53-2 spool insulators. Replacement component clevis bolt - P2070118P.



### Features

- 11/16" dia. mounting hole
- 5/8" dia. clevis pin
- Hot dip galvanized per ASTM A-153

### General

Coating	Galvanized, ASTM A-153
Material	Steel
Style	Sagger
Type	Insulated Secondary Clevis
UPC	096359014409

### Dimensions

Height	3.75 in
Length	4.00 in
Weight	2.31 lb

### Logistics

Pallet Quantity	600
-----------------	-----

### Product Assets

[Sales Drawings - Insulated Clevis \(SA2070116\)](#)  
[Technical Solutions - CH-C2070116-SPEC-EN](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
CH-C2070116-SPEC-EN | REV 1/2024