CHANCE®

27 kV, 125 kV BIL, Type C Standard Porcelain Cutout w/100A 8kAIC fuseholder

By Chance
Catalog # C710211E

27 kV, 125 kV BIL, Standard Type C Porcelain Cutout with a 100A, 8kAIC fuseholder, small eyebolt connector and no bracket.

Features

- Fully Compliant with ANSI/IEEE C37.41 & C37.42 – 2016
- Interchangeable with ABB Type ICX & S&C(MPS) Type XS
- Single Vent Solid Cap Design
- Uses Universal Style Fuse Links
- Synthetic Arc Quenching Fuse Holder Liner Material

General

Bracket Type	No Bracket
Catalog Number	C710211E
Description - Replacement Fuse Holder	T710-211T
Type	Cutout
UPC	096359029380

Dimensions

Dimensions	19.750 in x 13.250 in x 4.120 in
Height	4.12 in
Length	19.75 in
Weight	19.923 lb
Width	13.25 in

Electrical Ratings

BIL	125 kV
Creep and Leakage Distance	12.6″ (319mm)
Current Rating	100 A
Fuselink Current Range	1A to 100A
Reference Voltage Limit - Minimum	Thru 24.9kV
Temperature Rise - Max. at 300A	33° C
Voltage - Maximum	27 kV
Voltage - Radio Interference	Ambient @15.66kV
Voltage Rating	27 kV

Logistics

Pallet Quantity	48
Standard Package	1

Product Assets

Catalogs - Type C-Porcelain Cutouts
Installation Manuals - Standard Cutout Installation Instructions
Literature - Switching Line Card_FAQ_2019
Literature - HUBBELL® | CHANCE® RUS CUTOUT LISTING
Sales Drawings - 125KV BIL Cutout
Specifications - C710211E
Video - Hubbell Power Systems Cutout Seminar, Part 3: Quality
Video - Hubbell Power Systems Cutout Seminar, Part 2: Experience

©2024 Hubbell Incorporated. All rights reserved