

# 27 kV, 125 kV BIL, Type C Standard Porcelain Cutout w/200A 10kAIC fuseholder

By CHANCE Utility Catalog # C710242LXM

27 kV, 125 kV BIL, Standard Type C Porcelain Cutout with a 200A, 10kAIC fuseholder, large eyebolt connector and an extended NEMA "B" crossarm bracket.



\*Representative Image

### **Features**

- Fully Compliant with ANSI/IEEE C37.41 & C37.42 2016
- Interchangeable with ABB Type ICX & S&C(MPS) Type XS
- Single Vent Solid Cap Design
- Uses Universal Style Fuse Links
- Synthetic Arc Quenching Fuse Holder Liner Material

### General

crossarm

Description - Replacement T710-242TM

Fuse Holder

Type Cutout

**Dimensions** 

Weight 24.96 lb

# **Electrical Ratings**

BIL 125 kV

Creep and Leakage Distance 12.6" (319mm)
Current Rating 200 A

arrent rating 200 A

Fuselink Current Range 140A to 200A Reference Voltage Limit - Thru 24.9kV

Minimum

Temperature Rise - Max. at 33° C

300A

Voltage - Maximum 27 kV

Voltage - Radio Interference Ambient @15.66kV

Voltage Rating 27 kV

## Logistics

Pallet Quantity 48 EA Standard Package 1

## **Product Assets**

Catalogs - Type C-Porcelain Cutouts (10A)

Installation Manuals - Standard Cutout Installation Instructions

Literature - SF11036E\_HPS CHANCE RUS Cutout Listing

Literature - Switching Line Card\_FAQ\_2019 Sales Drawings - 125KV BIL Cutout (SA710-2)

Video - Hubbell Power Systems Cutout Seminar, Part 2:

Experience (VI10004E)

Video - Hubbell Power Systems Cutout Seminar, Part 3: Quality

(VI10005E)

