CHANCE®

36 kV, 170 kV BIL, Type C Standard Porcelain Cutout w/300A Solid Blade

By Chance
Catalog # C710733LBM

36 kV, 170 kV BIL, Standard Type C Porcelain Cutout with a 300A, 12kAIC solid blade, large eyebolt connector and a NEMA "B" crossarm bracket.

Features

- Fully Compliant with ANSI/IEEE C37.41 & C37.42 – 2016
- Interchangeable with ABB Type ICX & S&C(MPS) Type XS
- Single Vent Solid Cap Design
- Uses Universal Style Fuse Links
- Synthetic Arc Quenching Fuse Holder Liner Material

General

Bracket Type	NEMA "B" Heavy Duty for crossarm
Catalog Number	C710733LBM
Corrosion Resistant?	No
Description - Replacement Fuse Holder	T710-733TM
Type	Cutout

Dimensions

Weight	37.05 lb

Electrical Ratings

BIL	170 kV
Creep and Leakage Distance	28.4" (720mm)
Current Rating	300 A
Reference Voltage Limit - Minimum	Thru 34.5kV
Voltage - Maximum	36 kV
Voltage Rating	36 kV
Withstand Current - Short Time (10 cycles)	12,000 Amps Asym.

Logistics

Pallet Quantity	24 EA
Standard Package	1

Product Assets

Catalogs - Type C-Porcelain Cutouts
Installation Manuals - Standard Cutout Installation Instructions
Literature - Switching Line Card_FAQ_2019
Literature - HUBBELL® | CHANCE® RUS CUTOUT LISTING
Sales Drawings - 170KV BIL Cutout (730MM)
Specifications - C710733LBM
Video - Hubbell Power Systems Cutout Seminar, Part 3: Quality
Video - Hubbell Power Systems Cutout Seminar, Part 2: Experience

©2024 Hubbell Incorporated. All rights reserved