CHANCE®

27 kV, 125 kV BIL, Type C Standard Porcelain Cutout / Arrester Combination

By Chance
Catalog # C71DN242ED

27 kV, 125 kV BIL, Standard Type C Porcelain Cutout / Arrester Combination with a 200A, 10kAIC fuseholder, small eyebolt connector and a D-shape pole mounting bracket.

Features

- Fully Compliant with ANSI/IEEE C37.41 & C37.42 – 2016
- Interchangeable with ABB Type ICX & S&C(MPS) Type XS
- Single Vent Solid Cap Design
- Uses Universal Style Fuse Links
- Synthetic Arc Quenching Fuse Holder Liner Material
- Ohio Brass Distribution Class Arresters in Standard, Heavy and Riser Pole Duty Ratings

General

Bracket Type	D-shape for pole mounting
Catalog Number	C71DN242ED
Description - Replacement Fuse Holder	T710-242T
Type	Cutout

Electrical Ratings

BIL	125 kV
Creep and Leakage Distance	12.6″ (319mm)
Current Rating	200 A
Fuselink Current Range	140A to 200A
Reference Voltage Limit - Minimum	Thru 24.9kV
Temperature Rise - Max. at 300A	33° C
Voltage - Maximum	27 kV
Voltage - Radio Interference	Ambient @15.66kV
Voltage Rating	27 kV

Logistics

Pallet Quantity	18 EA
Standard Package	1

Product Assets

Catalogs - Type C-Porcelain Cutouts
Literature - Switching Line Card_FAQ_2019
Sales Drawings - 125 KV BIL Cutout / Arrester
Specifications - C71DN242ED
Video - Hubbell Power Systems Cutout Seminar, Part 3: Quality
Video - Hubbell Power Systems Cutout Seminar, Part 2: Experience

©2024 Hubbell Incorporated. All rights reserved