CHANCE®

# 15 kV, 110 kV BIL, Type C Linkbreak Porcelain Cutout w/100A 16kAIC fuseholder

By Chance
Catalog # C720114EB

15 kV, 110 kV BIL, Linkbreak Type C Porcelain Cutout with a 100A, 16kAIC fuseholder, small eyebolt connector and a NEMA "B" crossarm bracket.

## Features

- Fully Compliant with ANSI/IEEE C37.41 & C37.42 – 2016
- Interchangeable with ABB Type ICX & S&C(MPS) Type XS
- Single Vent Solid Cap Design
- Uses Universal Style Fuse Links
- Synthetic Arc Quenching Fuse Holder Liner Material

## General

| | |
|---|---|
| Bracket Type | NEMA "B" Heavy Duty for crossarm |
| Catalog Number | C720114EB |
| Description - Replacement Fuse Holder | T720-114T |
| Type | Cutout |
| UPC | 096359361596 |

## Dimensions

| | |
|---|---|
| Weight | 20.9 lb |

## Electrical Ratings

| | |
|---|---|
| BIL | 110 kV |
| Creep and Leakage Distance | 8.7" (220mm) |
| Current Rating | 100 A |
| Fuselink Current Range | 1A to 100A - removable buttonhead fuse link only |
| Reference Voltage Limit - Minimum | Thru 14.4kV |
| Temperature Rise - Max. at 300A | 38° C |
| Voltage - Maximum | 15 kV |
| Voltage - Radio Interference | Ambient |
| Voltage Rating | 15 kV |

## Logistics

| | |
|---|---|
| Pallet Quantity | 72 EA |
| Standard Package | 1 |

## Product Assets

Catalogs - Type C-Porcelain Cutouts
Installation Manuals - Link Break Cutout Installation Instructions
Literature - Switching Line Card_FAQ_2019
Literature - HUBBELL® | CHANCE® RUS CUTOUT LISTING
Sales Drawings - Cutout, Linkbreak 110 KV BIL
Specifications - C720114EB
Video - Hubbell Power Systems Cutout Seminar, Part 3: Quality
Video - Hubbell Power Systems Cutout Seminar, Part 2: Experience



©2024 Hubbell Incorporated. All rights reserved