# **CHANCE**®

## 22/36.4 kV, 150 kV BIL, Type C Linkbreak Porcelain Cutout / Arrester Combination w/100A 12kAIC fuseholder

By CHANCE Utility Catalog # C72DN313EBS

22/36.4 kV, 150 kV BIL, Linkbreak Type C Porcelain Cutout / Arrester Combination with a 100A, 12kAIC fuseholder, small eyebolt connector and a NEMA "B" crossarm bracket.

#### **Features**

- Fully Compliant with ANSI/IEEE C37.41 & C37.42 2016
- Interchangeable with ABB Type ICX & S&C(MPS) Type XS
- Single Vent Solid Cap Design
- · Uses Universal Style Fuse Links
- Synthetic Arc Quenching Fuse Holder Liner Material
- Ohio Brass Distribution Class Arresters in Standard, Heavy and Riser Pole Duty Ratings

#### General

Bracket Type NEMA "B" Heavy Duty for

crossarm Yes

Corrosion Resistant?

Description - Replacement T720-313T

Fuse Holder

Type Cutout



\*Representative Image

### **Electrical Ratings**

BIL 150 kV

Creep and Leakage Distance 17.3" (440mm)

Current Rating 100 A

Fuselink Current Range 1A to 100A - removable buttonhead fuse link only

Reference Voltage Limit - No Restrictions thru 20.8kV;

35° C

Minimum \*22.8 thru 34.5kV

Temperature Rise - Max. at 300A

Voltage - Radio Interference Ambient @22kV Voltage Rating 22/36.4 kV

Logistics

Standard Package

#### **Product Assets**

Catalogs - Type C-Porcelain Cutouts (10A) Literature - Switching Line Card FAQ 2019

Video - Hubbell Power Systems Cutout Seminar, Part 2: Experience (VI10004E)

Video - Hubbell Power Systems Cutout Seminar, Part 3: Quality (VI10005E)

