CHANCE

15 kV, 110 kV BIL, Type C Loadbreak Porcelain Cutout / Arrester Combination w/200A 12kAIC fuseholder

By CHANCE Utility Catalog # C73DM143EX

15 kV, 110 kV BIL, Loadbreak Type C Porcelain Cutout / Arrester Combination with a 200A, 12kAIC fuseholder, small eyebolt connector and an extended NEMA "B" crossarm bracket.

Features

- Fully Compliant with ANSI/IEEE C37.41 & C37.42 2016
- Interchangeable with ABB Type ICX & S&C(MPS) Type XS
- Single Vent Solid Cap Design
- Uses Universal Style Fuse Links
- Synthetic Arc Quenching Fuse Holder Liner Material
- Ohio Brass Distribution Class Arresters in Standard, Heavy and Riser Pole Duty Ratings
- Non Interchangeable Mounting Assembly

General

Bracket Type Extended NEMA "B" for

crossarm T730-143T

Description - Replacement

Fuse Holder

Type Cutout

*Representative Image

Electrical Ratings

BIL 110 kV

Creep and Leakage Distance 8.7" (220mm)

Current Rating 200 A

Fuselink Current Range 140A to 200A - removable

buttonhead fuse link only

Thru 14.4kV

Reference Voltage Limit -

Minimum

Temperature Rise - Max. at 39° C

300A

Voltage - Maximum 15 kV

Voltage - Radio Interference Ambient @ 9.41kV

Voltage Rating 15 kV

Logistics

Standard Package 1

Product Assets

Catalogs - Type C-Porcelain Cutouts (10A) Literature - Switching Line Card_FAQ_2019

Sales Drawings - 110KV BIL Loadbreak Cutout/Arrester (SA73DL1)

Technical Solutions - CH-C73DM143EX-SPEC-EN

Video - Hubbell Power Systems Cutout Seminar, Part 2:

Experience (VI10004E)

 $\begin{tabular}{ll} Video - Hubbell Power Systems Cutout Seminar, Part 3: Quality (VI10005E) \end{tabular}$

