CHANCE®

# 15/27 kV, 125 kV BIL, Type C Loadbreak Porcelain Cutout / Arrester Combination w/300A Solid Blade

By Chance
Catalog # C73EN233EB

15/27 kV, 125 kV BIL, Loadbreak Type C Porcelain Cutout / Arrester Combination with a 300A solid blade, small eyebolt connector and a NEMA "B" crossarm bracket.

## Features

- Fully Compliant with ANSI/IEEE C37.41 & C37.42 – 2016
- Interchangeable with ABB Type ICX & S&C(MPS) Type XS
- Single Vent Solid Cap Design
- Uses Universal Style Fuse Links
- Synthetic Arc Quenching Fuse Holder Liner Material
- Ohio Brass Distribution Class Arresters in Standard, Heavy and Riser Pole Duty Ratings
- Non Interchangeable Mounting Assembly

## General

| | |
|---|---|
| Bracket Type | NEMA "B" Heavy Duty for crossarm |
| Catalog Number | C73EN233EB |
| Description - Replacement Fuse Holder | T730-233T |
| Type | Cutout |

## Electrical Ratings

| | |
|---|---|
| BIL | 125 kV |
| Creep and Leakage Distance | 12.6" (319mm) |
| Current Rating | 300 A |
| Reference Voltage Limit - Minimum | No Restrictions thru 14.9kV; *20.8 thru 24.9kV |
| Temperature Rise - Max. at 300A | 40° C |
| Voltage - Radio Interference | 36.2 micro-volts @ 15.66kV |
| Voltage Rating | 15/27 kV |
| Withstand Current - Short Time (10 cycles) | 12,000 Amps Asym. |

## Logistics

| | |
|---|---|
| Standard Package | 1 |

## Product Assets

Catalogs - Type C-Porcelain Cutouts
Literature - Switching Line Card_FAQ_2019
Specifications - C73EN233EB
Video - Hubbell Power Systems Cutout Seminar, Part 3: Quality
Video - Hubbell Power Systems Cutout Seminar, Part 2: Experience



©2024 Hubbell Incorporated. All rights reserved